

METHOD AND DEVICE FOR SWITCHING A CONNECTION IN A
COMMUNICATION NETWORK

CLAIM FOR PRIORITY

5 This application claims priority to International
Application No. PCT/DE00/03328 which was filed in the
German language on September 25, 2000.

TECHNICAL FIELD OF THE INVENTION

10 The present invention relates to a method and device
for switching a connection between two subscribers of a
communication network, and in particular, for switching
a connection from an exchange of the communication
network using the existing switching functions and
15 signal transmission functions of the communication
network.

BACKGROUND OF THE INVENTION

A connection between two subscribers of a communication
20 network can be initiated by the two subscribers being
called separately from a special terminal located
outside the communication network, using a computer as
automatic operator. As soon as a connection exists to
both subscribers and the special terminal, the
25 information signals and the control signals for service
indicators, if any, are then transmitted by this
terminal from one connection to the other and
conversely. Such a switching method is used in
telephone networks in call centers. The disadvantageous
30 factor is the relatively complex implementation and the
necessary capacity for high performance required from
the special terminal.

Such switching of a connection in telephone networks is
35 of particular interest for the function of "click to
dial" out of the Internet. "Click to dial" is an offer
in the Internet in which a user of the Internet is
provided with the possibility of setting up a
connection directly by instruction between two

subscriber numbers of the telephone network, the telephone numbers of which are input or retrieved from a database. Both lines involved must be dialed for this and connected to one another. In most cases, one
5 subscriber is the Internet user himself.

If this function is implemented similar to the call switching in call centers, a controller operating as terminal of the communication network initiates two
10 connections via the communication network and, as soon as both connections exist, the controller must forwards the information data. That is, the digitized voice or other data to be transmitted, of one connection via the other one and conversely. To maintain the features
15 offered by the communication system used in the communication network, e.g. the service indicators of the ISDN in the telephone network, for both subscribers of the initially different connections, must be transferred from one connection to the second one and
20 adapted, if necessary. This creates considerable expenditure since the computer receives the service indicators like a terminal and forwards them again to the second corresponding connection like a terminal. Additional computing effort is produced by the fact
25 that some data have to be converted and adapted. In the ISDN, for example, it is possible to indicate the telephone number of the other subscriber by means of the CLIP feature. Since there are two connections from the point of view of the communication network, the
30 second call must receive from the controller the indicator of the telephone number of the first call instead of that belonging to the controller, in order to guarantee this feature.

35 It is also desirable to have a capability of integrating the "click to dial" service with the simplest possible means also in existing network nodes in the case where a network operator itself offers this service.

Figure 1 shows in accordance with the prior art the switching of a connection in a communication network by a computer connected to the communication network as terminal which is used as automatic operator 9. The communication network transit exchanges 3 and some access exchanges 4. An exchange center can have both functions and can be both transit exchange 3 and access exchange 4. The transit exchanges are connected to one another by means of transmission links which have at least one information channel 5 and at least one separate signaling channel 6. Figure 1 shows the connection between a first subscriber 7 and a second subscriber 8 by the automatic operator 9. The automatic operator 9 first dials both subscribers 7, 8 in two separate connections via two terminal lines 14. In the example shown, both connections initially take the same path. From the access exchange 4 of the automatic operator 9, they first reach the same transit exchange 3. Depending on the subscriber 7, 8 dialed, the connections can also take separate paths through the communication network after the access exchange 4 to which the automatic operator 9 is connected. In the transit exchange 3, the two connections are switched through completely independently as two different ones. This happens by the information channels 5 and signaling channels 6 being conducted via line trunk groups 2 in the transit exchange 3 and being switched through in a switching network 1 according to the control signals in the signaling channels 6.

If the two connections to the first subscriber 7 and second subscriber 8 have been established, the automatic operator 9 connects the two connections.

35 SUMMARY OF THE INVENTION

In one embodiment of the invention, there is a method for switching a connection between two subscribers of a communication network with a common signaling channel which is independent of the

- 6 -

those for PCM24 transmission links.

In another aspect of the invention, the controller is an existing controller of the transit exchange.

In still another aspect of the invention, the transit exchange is a transit exchange of the EWSD system and the inputs are connected by two accesses for PCM lines in each case being connected at one line trunk group.

In another aspect of the invention, the controller is a group processor of the line trunk group.

In another aspect of the invention, the controller is connected to a network server which is connected to another communication network to initiate the connection by a program on the network server after a request from the other communication network.

In yet another aspect of the invention, the other communication network is the Internet.

BRIEF DESCRIPTION OF THE DRAWINGS

5 In the text which follows, the invention will be explained with reference to the figures in which:

Figure 1 shows the connection of two subscribers by a third party according to the prior art, by a computer
10 as terminal of the network.

Figure 2 shows the connection between two subscribers by a third party by means of the device according to
15 the invention.

Figure 3 shows an embodiment according to the invention of the device in a transit exchange EWSD.

20 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

The invention provides a method and a device by means of which it is possible without elaborate adaptations of the transit exchanges and the modules and facilities used in them to establish a connection between two

According to one embodiment of the invention, there is a method for switching a connection between two subscribers in a communication network with a common signaling channel which is independent of the information channels and with transit exchanges including at least one switching network and associated line trunk groups is provided, the switching being effected after the connection has been requested from a third party.

Initially, two inputs for transmission links at a transit exchange are connected by a data line. This can already been done by means of a signal data line. This also results in a permanent allocation of the information data channels in pairs, for example the voice channels in a telephone network. In networks operating with a synchronous digital hierarchy or a plesiochronous digital hierarchy on the transmission links or generally in the case of multiplex lines, at least one information channel of one input is permanently allocated to an information channel of the other input of the transmission link via the corresponding timeslot. Naturally, it is also possible, in an ATM network, to achieve a fixed paired information channel allocation by means of such a hardware connection of the inputs of transmission links by utilizing the coding and decoding methods provided by the network since for each transit exchange a transmission link, which, in turn, is connected to the exchange itself, acts in such a manner as if it were connected to an adjacent transit exchange. Thus, the methods already in existence produce a fixed information channel allocation since an unambiguous defined information channel allocation must also exist between transit exchanges.

15 Finally, the incoming terminal signaling of the connection to the first subscriber in one call are forwarded to the connection to the second subscriber via the common signaling channel and conversely.

20 This can be advantageously carried out with relatively
little expenditure even at transit exchanges already
existing. Since the junction line is not a terminal and
thus does not generate its own terminal signaling, the
full extent of the features of the protocol used can already
25 be secured between the terminals by a simple forwarding
of the terminal signaling. If, for example, the call
number of one subscriber is transmitted via the
signaling and forwarded to the other connection via the
common signaling channel, the desired result is
30 obtained without further translation of the signaling.
Transmission of the information data does not require
any expenditure since the transit exchange in the
method according to the invention sees itself as an
apparent adjacent transit exchange and, as a result,
35 ensures synchronization of the information channels and
transmission of the information data by means of the
preexisting methods and devices.

In one aspect of the invention, the ITU-T signaling

- 9 -

system No. 7 is advantageously used for the signaling on the common signaling channel.

5 In another aspect of the invention, the signaling messages of the ISDN User Part (ISUP) are advantageously transmitted from the first connection to the second connection and conversely via the ITU-T signaling system No. 7.

10 The control signals are preferably generated by an existing controller of the transit exchange and forwarded to the common signaling channel. As a result, the method described can be applied with little expenditure by a corresponding program without needing
15 an additional controller if the computing power of existing controllers is adequate.

It is also advantageous to use as inputs those for transmission links of the PCM30 or PCM 24 type of
20 construction. Since these two types of transmission links are in most cases used in existing transit exchanges, corresponding inputs exist. As a result, it is possible in a relatively simple way to apply the method described to transit exchanges already in
25 existence.

According to the invention, a connection can be initiated in a similar manner by a request from another communication network. For this purpose, a program
30 installed on a computer which is connected to the other communication network issues the instruction for setting up the connection. In particular, the "click to dial" feature can thus be implemented if the other communication network is the Internet.

35

In one embodiment, a device in a transit exchange is provided for switching a connection between two subscribers in a communication network. The communication network exhibits a common signaling

- 10 -

channel which is independent of the information channels. Furthermore, this is a communication network with transit exchanges consisting of in each case at least one switching network and associated line trunk
5 groups.

At least one pair of information channels is permanently allocated for information data by at least one connection between two inputs for transmission
10 links at the transit exchange by means of a data line.

Furthermore, the device includes a controller (CTD controller) which is connected to the common signaling channel and which conducts on the common signaling
15 channel a control signal having the content that a connection is present on one information channel of the information channels in each case permanently allocated to one another, which connection is switched through to one subscriber, and a connection is present on the
20 second information channel of the information channels in each case permanently allocated to one another, which connection is switched through to the second subscriber. The controller forwards the terminal signaling of the connection to the first subscriber to
25 the connection to the second subscriber and conversely.

A connection between two subscribers of the communication network can be set up with little expenditure since it is the computing effort for
30 generating the signals of the common signaling channel and the transmission of the terminal signaling by the controller which are produced. The transit exchange in the device according to the invention sees itself as an apparent adjacent transit exchange and the
35 synchronization of the information data and the permanent allocation of the information channels is thus effected with the existing means of the transit exchange.

- 13 -

signal on the signaling channel 6. Since the transit exchange 3 sees itself as an adjacent transit exchange via the information channels 5 and the data line 12, the information channels 5 are permanently allocated to one another via the synchronizing devices and methods normally existing between the transit exchanges and transmit the information data. The controller 10 also transmits, on the signaling channel 6, terminal signaling messages coming from the connection to the first subscriber 7 to the connection to the second subscriber 8 and conversely.

Compared with the prior art, the embodiment of the device according to the invention described has the advantage that it can be set up with little expenditure and also subsequently in an existing transit exchange 3. It is only necessary to install the data line 12, to supplement an existing controller by software adaptation to the controller 10 and to set up an interface as junction line 11 to a network server 13. This can also be done by utilizing existing system interfaces to the outside.

Figure 3 shows in a simplified manner a further embodiment according to the invention of the device described above in a transit exchange of the EWSD type.

A transit exchange of the EWSD type consists of a switching network 1 (SN) and at least one line trunk group 2 (LTG). In this case, four are shown, one of which is drawn enlarged and with its modules. The switching network 1 has, for the control function, its own controller, the switch group control 15 (SGC). A line trunk group 2 is built up of line trunk units 17 (DIU,LTU), a group switch 19 and a line interface unit 20. If the line trunk group 2 is designed for PCM30 transmission links as in the embodiment shown, the line trunk group 2 has four line trunk units 17. Each line trunk unit 17 provides a PCM30 access 22 for a

- 14 -

transmission link. In each case two of the PCM30
 accesses 22 are connected to one another by data lines
 12. The group processor 21 is at the same time the
 signal processor 10. The line trunk units 17 combine
 5 the information channels in a group switch 19 (GS).
 Four 2-MBit PCM lines of 32 information channels each
 are combined in the group switch 19 to form an 8-MBit
 line with 128 channels which are forwarded to the
 switching network 1 via the interface of the line
 10 interface unit 20. The connection is set up as already
 described above. Since the group processor 21 is
 connected to the processor of the switching network 1,
 the switch group control 15 and the central processor
 16 via internal interfaces, it can be used as
 15 controller 10. The software must be appropriately
 adapted. The instruction for setting up a connection to
 the controller 10 can also be transmitted via these
 interfaces. Using the embodiment described, it is,
 therefore, possible to establish the device according
 20 to the invention by means of two data lines 12 and a
 software supplement. In particular, subsequent
 installation in existing transit exchanges EWSD which
 are used in large numbers is also conceivable.